



02.04 – OPERATIONAL SPECIFICATIONS

Table 02.04.01 Operational Specifications of the Machine

Specifications	TMH 200
Air Pressure [bar]	6
Air Consumption [lt/minute]	50
Mixture Proportion Range [lt]	1/5 – 1/15
Big Material Tank Capacity [lt]	200
Small Material Tank Capacity [lt]	20
Material Flow Speed [lt/minute @ 250 bar]	1,5
Operating Temperature Range [°C]	- 35 / + 45
Big Cylinder Pressure [bar]	6
Arm Cylinder Pressure [bar]	15 – 20
Small Cylinder Pressure [bar]	4
Noise Emission Level	75 dB (A) K (uncertainty of measurement) : 4 dB (EN ISO 3746)

Tablo 02.04.01 Hidrolik Veriler

ÖZELLİK	TMH 200
Max Hydraulic Pressure [bar]	200
Operating Pressure [bar]	60
Oil Storage Capacity [lt]	90
Hydraulic Oil Types	SHELL TELLUS 68 MOBİL DTE OİL 26 BP HLP HM 68 SELENIA HİDROBAK 68 CASTROL HYSPIIN 68
Hydraulic Pump Unit Motor Power [kW]	3
Hydraulic Pump Capacity [lt/minute]	16