

## Ecostar 250

The economic version

### Ecostar 250

Dosing and  
metering plant  
for manifold  
industrial  
applications



Its state-of-the-art technology at a favourable price simply make this machine a star for manifold industrial applications. Beyond that the Ecostar 250 is designed for use in the most constricted of space.

Both the high operating reliability and easy maintainability provide its all-round quality. Thus thanks to the new design of the drum grip changing drums is now easier than ever before. In the same way the special construction of the follow plate makes it possible to empty the material drum to an absolute minimum residue - this not only makes the Ecostar 250 environment-friendly but also cuts costs twice.

The economic hydraulic drive guarantees constant output at low-noise operations.

In addition to the extensive standard equipment you can arrange your machine to your individual requirements thanks to the large range of options.

Security as to the process  
Stable as to quality





**Standard Equipment**

- Adjustable mixing ratio
- Dosage control device
- Material shortage control
- Over-pressure safety device
- Follow plate for reduced residue
- Mixing unit Alpha-Mix for PS with 2 mixing chambers
- Mixing unit Alpha-Mix for PU/SI with 3 mixing chambers
- Mixing unit Alpha-Mix for SI with anit-adhesive coating
- Low-maintenance dosing pump sealing system
- Hydraulic dosing pump drive
- Empty drum warning system for component A
- 200 l drum garage for ergonomic drum change
- Relay control
- Pot life control
- Follow plate heating unit for component A (PS/PU only)
- Two-hand control unit for 200 l drum press

**Options**

- Swivel arm, 3.500 mm long
- Application manipulator, 3.300 mm long
- Swivel arm heating component A, 3.500 mm long
- Heating componente A up to swivel arm
- Cartridge filler facility
- Feeding pump component B for 200 l drum (PU only)
- Extension hose (PS/PU) extra charge per m
- Extension hose (SI) extra charge per m
- Special coat of lacquer

**Additional Equipment**

- Rinsing pump for sovent
- Freezer NF 1.0 - 25/50 /PU/PS/SI

With the kind support of:  
 - Viessmann France SAS  
 - Eura Mobil GmbH  
 - Kaba Gallenschütz GmbH  
 - Dow Corning

**Technical Data**

Output	ca. 2.500 g/min (for polysulphide) (depending on material viscosity)
Mixing ratio volumetric	100:16,6 to 100:7 continuously adjustable; different mixing ratios are also available at exchange of pump
Connected loads electrical	3 x 400 V, PE, N, 50 Hz, 1,7 - 6,5 kW (if required also special voltage)
Connected loads pneumatic	6 bar, max. 30 l/min
Dimensions (L x B x H1, H2, H3) H1: loading height, H2: max. working height, H3: height swivel arm	1.380 x 1.215 x 1.850, 3.500, 2.800
Weight	ca. 580 kg

Reinhardt-Technik GmbH

Waldheimstr. 3, D-58566 Kierspe  
 Postfach 1207, D-58555 Kierspe

Fon +49 (0)2359 666-0

Fax +49 (0)2359 666-129

Internet:

<http://www.reinhardt-technik.de>

E-Mail:

[info@reinhardt-technik.de](mailto:info@reinhardt-technik.de)

